

## 715 Woven Aramid Tape

### Technical Data Sheet

# 715



#### General Description

Aramid fabric provides excellent abrasive and tear resistance in addition to good impact resistance due to its ability to absorb and dissipate energy. Woven aramid tape is excellent for providing extra strength in localised high wear areas such as canoe and kayak keel lines, etc. 0.39mm thickness. Available in 50mm and 75mm widths.

715-5 5m of 50mm wide 200g/m<sup>2</sup> Plain Weave Aramid Tape

715-10 10m of 50mm wide 200g/m<sup>2</sup> Plain Weave Aramid Tape

715-50 50m of 50mm wide 200g/m<sup>2</sup> Plain Weave Aramid Tape

#### Characteristics

Width .....	50mm
Weight .....	200g/m <sup>2</sup>
Fibre Orientation.....	0°/90°
Warp .....	50%
Weft .....	50%
Approximate thickness.....	0.39mm
Cured Appearance .....	Yellow
Ends cm .....	6.00
Picks cm.....	4.00
Warp Fibre .....	Kevlar 185
Weft Fibre.....	Kevlar 185

West System International  
Cupernham House  
Cupernham Lane  
Romsey, Hampshire  
SO51 7LF, UK

+44(0)1794 521111

[westsystem.co.uk](http://westsystem.co.uk)

ISO9001:2008 Certified

REV 1 / Nov, 2016

These are typical properties and cannot be construed as a specification. The end users should test the products to ensure the products are suitable for the intended application. Any information, data, advice or recommendation published by Wessex Resins by other means and whether relating to Wessex Resins' materials or other materials, is given in good faith and believed to be reliable.